

INDEX MS32C

Kind : Cnc multispindle lathe
Manufacturer : INDEX
Model : MS32C
Year : 2004
Serial : 150292
Stock : 9672



TECHNICAL DETAILS

- | | |
|---|--|
| - number of spindles | : 6 independent |
| - bar clearance | : 32 [mm] |
| - maxi spindle speed | : 6 300 [rpm] |
| - machine equipped with 32 numerical axes | |
| - slide unity 1.1 | : X and Z axes controlled by CNC |
| - slide unity 1.2 | : fixed X axis, Z axis controlled by CNC |
| - slide unity 2.1 | : fixed X axis, Z axis controlled by CNC |
| - slide unity 2.2 | : X and Z axes controlled by CNC |
| - slide unity 3.1 | : X and Z axes controlled by CNC |
| - slide unity 3.2 | : fixed X axis, Z axis controlled by CNC |
| - slide unity 4.1 | : X and Z axes controlled by CNC |
| - slide unity 4.2 | : fixed X axis, Z axis controlled by CNC |
| - slide unity 5.1 | : fixed X axis, Z axis controlled by CNC |
| - slide unity 5.2 | : X and Z axes controlled by CNC |
| - slide unity 6.1 | : X and Z axes controlled by CNC |
| - slide unity 6.2 | : X and Z axes controlled by CNC |
| - counter-spindle in position 6.1 | : X and Z axes controlled by CNC |

Kind : Cnc multispindle lathe

Manufacturer : INDEX

Model : MS32C

Year : 2004

Serial : 150292

Stock : 9672

EQUIPMENT

- INDEX C200-4 (Siemens SINUMERIK 840D)
- Simple NCU
- IEMCA SIR 32/33/P bar loader
- Coolant tank with HP pump
- KNOLL chips conveyor
- RIEDEL cooling unit
- Parts catcher with conveyor in position 6.1
- Cross rilling device in position 3.1 et 4.1